

NewAir I.B[®] Express

Inflatable Cushioning System

Patented Technology Ensures Fast, Reliable Inflatable Cushioning NewAir I.B.[®] Express packaging systems automatically inflate and dispense patented Barrier Bubble[™] cushioning material whenever and wherever you need it. Designed to withstand the rigors of today's global shipping environments, NewAir I.B.[®] Express inflatable material maintains its excellent cushioning properties throughout the entire shipping cycle.



NewAir I.B[®] Express

Inflatable Cushioning System

Patented Technology Ensures Fast, Reliable Inflatable Cushioning



Telford Way Kettering NN16 8UN United Kingdom



T: +44 1536 315700 F: +44 1536 410576 E: info-pack@sealedair.com www.sealedairprotects.eu

ON-SITE, ON-DEMAND, HIGH PERFORMANCE CUSHIONING WITH OPTIMUM FLEXIBILITY

THE DIFFERENCE IS IN THE BARRIER BUBBLE[™] TECHNOLOGY

The Sealed Air proprietary film technology retains air longer than non-barrier polyethylene air cellular materials and out-performs other materials for



cushioning and overall packaging protection.

BENEFITS OF NEWAIR I.B® EXPRESS

- Fast & flexible Dispenses 10.8 m² of inflatable cushioning per minute; adapts to any work cell environment at speeds up to 20 metres per minute.
- Completely portable No shop air required.
- Easy to operate Just plug it in, power it up, load a roll of film and let it run.
- Film options Available in two different film widths of premium and regular film quality and a variety of bubble sizes as well as Anti-Static film.
- Cost effective, saves space Frees up valuable warehouse space. Makes the equivalent of a trailer load of traditional air cellular materials with just 20 rolls of our 610 metre film.

The NewAir I.B.[®] Express is supported by a range of accessories including SystemStand[™], Roll Winder[™], Jet Stream[®] delivery system and Instasheeter[™] converting system, making it flexible enough to be used in every packaging operation.

SPECIFICATIONS

Dimensions (with standard width roll)	L77 x W67 x H46cm
Weight (without roll)	36.7 Kg.
Electrical	220/240 VAC 50 Hz 2A, Single Phase
Distributed by:	

Corporate office: Sealed Air Corporation, 200 Riverfront Boulevard, Elmwood Park, NJ 07407, USA www.sealedair.com Sealed Air has companies throughout the world.

© Sealed Air Corporation 2014. All rights reserved.

Packaging Supplies & Equipment INATECH CONCEPT S.R.L.

Domne[ti - Ilfov: 393, Tudor Vladimirescu Street Oradea: 271, Calea Clujului Street +40 21 4.480.358 office@ inatech.ro

www.inatech.ro www.inatech-shop.ro